


PRISMA V PAG. 7/8/9




dati tecnici per elemento / technical data per section / mesures techniques pour élément / detalles técnicos por elemento

| altezza height hauteur altura (H) mm | larghezza width largeur anchura (L) mm | interasse interspace interaxe interaje (I) mm | peso weight poids peso kg | contenuto d'acqua water content contenu d'eau contenido de agua l | resa output rendement rendimiento watt ΔT 30°C | resa output rendement rendimiento watt ΔT 50°C |
|--|--|---|---------------------------------------|---|--|--|
| 400 | 40 | 340 | 0,91 | 0,14 | 40 | 78 |
| 500 | 40 | 440 | 1,08 | 0,16 | 47 | 92 |
| 600 | 40 | 540 | 1,24 | 0,19 | 55 | 108 |
| 700 | 40 | 640 | 1,41 | 0,21 | 63 | 124 |
| 800 | 40 | 740 | 1,58 | 0,24 | 70 | 137 |
| 900 | 40 | 840 | 1,74 | 0,26 | 78 | 153 |
| 1000 | 40 | 940 | 1,91 | 0,29 | 85 | 167 |
| 1200 | 40 | 1140 | 2,24 | 0,34 | 101 | 199 |
| 1400 | 40 | 1340 | 2,58 | 0,39 | 117 | 229 |
| 1600 | 40 | 1540 | 2,90 | 0,44 | 132 | 259 |
| 1800 | 40 | 1740 | 3,24 | 0,49 | 147 | 289 |
| 2000 | 40 | 1940 | 3,57 | 0,54 | 163 | 319 |
| 2200 | 40 | 2140 | 3,90 | 0,59 | 177 | 348 |
| 2500 | 40 | 2440 | 4,40 | 0,67 | 200 | 392 |

Per tutto quello qui non specificato, si prega di contattare l'ufficio commerciale/tecnico della K8 radiatori . For anything not specified here, kindly contact the Sales/Technical Dept. of K8 Radiatori.

PRISMA O PAG. 10/11/13



dati tecnici per elemento / technical data per section / mesures techniques pour élément / detalles técnicos por elemento

| altezza height hauteur altura (H) mm | larghezza width largeur anchura (L) mm | interasse interspace interaxe interaje (I) mm | peso weight poids peso kg | contenuto d'acqua water content contenu d'eau contenido de agua l | resa output rendement rendimiento watt ΔT 30°C | resa output rendement rendimiento watt ΔT 50°C |
|--|--|---|---------------------------------------|---|--|--|
| 40 | 400 | 340 | 0,91 | 0,14 | 27 | 53 |
| 40 | 500 | 440 | 1,08 | 0,16 | 32 | 62 |
| 40 | 600 | 540 | 1,24 | 0,19 | 38 | 74 |
| 40 | 700 | 640 | 1,41 | 0,21 | 43 | 84 |
| 40 | 800 | 740 | 1,58 | 0,24 | 47 | 93 |
| 40 | 900 | 840 | 1,74 | 0,26 | 53 | 104 |
| 40 | 1000 | 940 | 1,91 | 0,29 | 58 | 114 |
| 40 | 1200 | 1140 | 2,24 | 0,34 | 69 | 135 |
| 40 | 1400 | 1340 | 2,58 | 0,39 | 80 | 156 |
| 40 | 1600 | 1540 | 2,90 | 0,44 | 90 | 176 |
| 40 | 1800 | 1740 | 3,24 | 0,49 | 100 | 196 |
| 40 | 2000 | 1940 | 3,57 | 0,54 | 111 | 217 |
| 40 | 2200 | 2140 | 3,90 | 0,59 | 121 | 237 |
| 40 | 2500 | 2440 | 4,40 | 0,67 | 136 | 266 |

Per tutto quello qui non specificato, si prega di contattare l'ufficio commerciale/tecnico della K8 radiatori . For anything not specified here, kindly contact the Sales/Technical Dept. of K8 Radiatori.