


## POWER COCO PAG. 40 / 41



altezza height hauteur altura (H) mm	larghezza width largeur anchura (L) mm	interasse interspace interaxe intereje (I) mm	peso weight poids peso kg	contenuto d'acqua water content contenu d'eau contenido de agua l	resa output rendement rendimiento watt $\Delta T$ 30°C	resa output rendement rendimiento watt $\Delta T$ 50°C
1200	480	1160	24	2,4	673	1320
	560	1160	27	2,8	787	1543
	640	1160	30	3,2	901	1766
1400	480	1360	27	2,7	779	1527
	560	1360	31	3,1	909	1783
	640	1360	34	3,6	1040	2040
1600	480	1560	30	3,0	884	1733
	560	1560	34	3,5	1032	2024
	640	1560	39	4,0	1180	2314
1800	480	1760	33	3,3	989	1940
	560	1760	38	3,9	1155	2264
	640	1760	43	4,4	1320	2588
2000	480	1960	37	3,6	1095	2147
	560	1960	42	4,2	1277	2504
	640	2160	47	4,8	1460	2862
2200	480	2160	40	3,9	1204	2361
	560	2160	46	4,6	1405	2754
	640	2160	51	5,2	1605	3148

Per tutto quello qui non specificato, si prega di contattare l'ufficio commerciale/tecnico della K8 radiatori . For anything not specified here, kindly contact the Sales/Technical Dept. of K8 Radiatori.