


YIN&YANG COCO PAG. 40 / 41



altezza height hauteur altura (H) mm	larghezza width largeur anchura (L) mm	interasse interspace interaxe intereje (l) mm	peso weight poids peso kg	contenuto d'acqua water content contenu d'eau contenido de agua l	resa output rendement rendimiento watt ΔT 30°C	resa output rendement rendimiento watt ΔT 50°C
1200	480	1080	18	1,9	388	761
	560	1080	21	2,3	466	914
	640	1080	23	2,6	545	1068
1400	480	1280	20	2,1	453	889
	560	1280	23	2,6	545	1068
	640	1280	26	3,0	636	1247
1600	480	1480	23	2,4	519	1017
	560	1480	26	2,9	623	1221
	640	1480	29	3,4	727	1425
1800	480	1680	25	2,6	583	1144
	560	1680	29	3,2	701	1374
	640	1680	32	3,7	818	1603
2000	480	1880	27	2,9	649	1272
	560	1880	31	3,5	778	1526
	640	1880	35	4,1	908	1781
2200	480	2080	30	3,2	717	1405
	560	2080	34	3,8	859	1685
	640	2080	38	4,4	1003	1966

Per tutto quello qui non specificato, si prega di contattare l'ufficio commerciale/tecnico della K8 radiatori . For anything not specified here, kindly contact the Sales/Technical Dept. of K8 Radiatori.