


YIN&YANG ECLIPSE PAG. 38 / 39



altezza height hauteur altura (H) mm	larghezza width largeur anchura (L) mm	interasse interspace interaxe intereje (l) mm	peso weight poids peso kg	contenuto d'acqua water content contenu d'eau contenido de agua l	resa output rendement rendimiento watt ΔT 30°C	resa output rendement rendimiento watt ΔT 50°C
1200	320	1080	11	1,1	232	454
	400	1080	15	1,5	310	607
	480	1080	18	1,9	388	761
	560	1080	21	2,3	466	914
	640	1080	23	2,6	545	1068
1400	320	1280	13	1,3	271	531
	400	1280	17	1,7	362	710
	480	1280	20	2,1	453	889
	560	1280	23	2,6	545	1068
	640	1280	26	3,0	636	1247
1600	320	1480	14	1,4	310	608
	400	1480	19	1,9	414	812
	480	1480	23	2,4	519	1017
	560	1480	26	2,9	623	1221
	640	1480	29	3,4	727	1425
1800	320	1680	15	1,6	350	686
	400	1680	21	2,1	467	915
	480	1680	25	2,6	583	1144
	560	1680	29	3,2	701	1374
	640	1680	32	3,7	818	1603
2000	320	1880	16,5	1,7	400	780
	400	1880	17	2,3	519	1018
	480	1880	27	2,9	649	1272
	560	1880	31	3,5	778	1526
	640	1880	35	4,1	908	1781
2200	320	2080	18	1,9	428	856
	400	2080	19	2,5	573	1124
	480	2080	30	3,2	717	1405
	560	2080	34	3,8	859	1685
	640	2080	38	4,4	1003	1966

Per tutto quello qui non specificato, si prega di contattare l'ufficio commerciale/tecnico della K8 radiatori . For anything not specified here, kindly contact the Sales/Technical Dept. of K8 Radiatori.